

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 10738-6-2 (1991): Flanges for Waveguides, Part 6:
Flanges for Square Waveguides, Section 2: Flange Type K
[LITD 6: Wires, Cables, Waveguides and Accessories]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक

तरंग पथकों के फ्लैजों की विशिष्टि

भाग 6 वर्गाकार तरंग पथकों के लिये फ्लैज

अनुभाग 2 फ्लैज टाइप के

Indian Standard

**SPECIFICATION FOR
FLANGES FOR WAVEGUIDES**

PART 6 FLANGES FOR SQUARE WAVEGUIDES

Section 2 Flange Type K

UDC 621.372.831 : 621.372.829

© BIS 1991

**BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002**

July 1991

Price Group 2

FOREWORD

This Indian Standard (Part 6/Sec 2) was adopted by the Bureau of Indian Standards, after the draft finalized by the Microwave Components and Accessories Sectional Committee had been approved by the Electronics and Telecommunication Division Council.

This standard (Part 6/Sec 2) shall be read in conjunction with IS 10738 (Part 1) : 1983, 'Flanges for waveguides: Part 1 General requirements and tests' and IS 10738 (Part 6/Sec 1) : 1991 'Flanges for waveguides: Part 6 Flanges for square waveguides, Section 1 General'.

Different types of waveguide flanges are being covered in a series of standards consisting of the following individual parts of IS 10738:

- Part 1 General requirements and tests
- Part 2 Flanges for ordinary rectangular waveguides
- Part 3 Flanges for flat rectangular waveguides
- Part 4 Flanges for flat circular waveguides
- Part 5 Flanges for medium flat rectangular waveguides
- Part 6 Flanges for square waveguides

This Part 6 of IS 10738 series is being issued in 2 Sections as follows:

- Section 1 General
- Section 2 Flange Type K

While preparing this standard assistance has been derived from IEC Pub 154-7 (1974) 'Flanges for waveguides : Part 7 Relevant specification for flanges for square waveguides', issued by the International Electrotechnical Commission (IEC).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard***SPECIFICATION FOR
FLANGES FOR WAVEGUIDES****PART 6 FLANGES FOR SQUARE WAVEGUIDES****Section 2 Flange Type K****1 SCOPE**

This Indian Standard (Part 6/Sec 2) lays down dimensional requirements for flange Type K for square waveguides.

2 REFERENCES

The following Indian Standards are necessary adjuncts to this standard:

<i>IS No.</i>	<i>Title</i>
4493 (Part 6) : 1982	Hollow metallic waveguides : Part 6 Rigid square waveguides
10738 (Part 1) : 1983	Flanges for waveguides : Part 1 General requirements and tests
10738 (Part 6/Sec 1) : 1991	Flanges for waveguides : Part 6 Flanges for square waveguides, Section 1 General

3 CLIMATIC CATEGORIES

Provisions of 3 of IS 10738 (Part 1) : 1983 shall apply.

**4 MATERIALS, CONSTRUCTION AND
WORKMANSHIP**

Provisions of 4 of IS 10738 (Part 1) : 1983 shall apply.

**5 DESIGNATION OF FLANGES FOR
WAVEGUIDES**

Provisions of 5 of IS 10738 (Part 1) : 1983 shall apply.

6 MARKING

Provisions of 6 of IS 10738 (Part 1) : 1983 shall apply.

7 PACKING

Provisions of 7 of IS 10738 (Part 1) : 1983 shall apply.

8 DIMENSIONAL REQUIREMENTS

The outline and dimensions for pressurizable and unpressurizable Type K flanges shall be in accordance with Fig. 1 and Table 1.

9 TESTS

Provisions of 8 of IS 10738 (Part 6/Sec 1) : 1991 shall apply.



FIG. 1 FLANGE TYPE *K*

Table 1 Dimensions of Type K Flanges for Square Waveguides
(Clause 8.1)

TYPE K FLANGES																					
Type Designation of Waveguide Flanges (IS : 10738)		To be Used with Waveguide	Locating Holes										Dimensions for Locating Bolts						Gasket Groove		
			Dia- meter D_{basic}	Fit	Deviation		a_1-b_1	G	H	X	R_{max}	2E	2F	2Z	Positional tolerance	Shank diameter basic	Fit	Deviation		J Position	
					Lower	Upper												Lower			Upper
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	All dimensions in millimetres.				(13)	(14)	(15)	(16)	(17)	(18)	(19)			
UKQ	41	Q41	6.350	B9	+0.150	+0.186	52.060	91.0	87.0	10.0	1.0	40.00	78.00	0.15	6.350	h8	-0.022	0	64.0		
	49	Q49	6.350	B9	+0.150	+0.186	44.060	80.0	76.0	10.0	1.0	27.00	65.20	0.15	6.350	h8	-0.022	0	52.1		
	54	Q54	5.000	B9	+0.140	+0.170	40.060	69.0	65.0	10.0	1.0	23.80	57.40	0.14	5.000	h8	-0.018	0	46.9		
	61	Q61	5.000	B9	+0.140	+0.170	36.060	66.0	62.0	10.0	1.0	21.00	52.60	0.14	5.000	h8	-0.018	0	42.5		
PKQ	65	Q65 ³	5.000	B9	+0.140	+0.170	34.060	65.0	61.0	10.0	1.0	24.00	51.00	0.14	5.000	h8	-0.018	0	42.0		
	70	Q70	4.000	C9	-0.070	-0.100	31.250	59.0	55.0	7.5	0.8	19.80	47.60	0.07	4.000	h8	-0.018	0	38.0		
	75	Q75	4.000	C9	+0.070	-0.100	29.250	57.0	53.0	7.5	0.8	19.00	45.60	0.07	4.000	h8	-0.018	0	36.0		
	85	Q85	4.000	C9	+0.070	-0.100	26.25	54.0	50.0	7.5	0.8	17.60	42.60	0.07	4.000	h8	-0.018	0	33.0		
	100	Q100	4.000	C9	-0.070	-0.100	22.75	50.0	46.0	7.5	0.8	16.20	39.20	0.07	4.000	h8	-0.018	0	29.5		
	115	Q115	4.000	C9	+0.070	+0.100	19.54	47.0	43.0	7.5	0.65	15.00	36.00	0.07	4.000	h8	-0.018	0	26.3		
	130	Q130	4.000	C9	-0.070	+0.100	17.54	45.0	41.0	7.5	0.50	14.00	34.00	0.07	4.000	h8	-0.018	0	24.3		

¹ See 8.3.11 of IS 10738 (Part 1) : 1983.

² These dimensions are not essential for the mating of two assemblies.

³ Not a preferred type.

Standard Mark

The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc : No. LTD 19 (1143)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha
(Common to all Offices)

Regional Offices :

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	{ 331 01 31 331 13 75
Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	37 86 62
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	53 38 43
Southern : C. I. T. Campus, IV Cross Road, MADRAS 600113	235 02 16
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093	6 32 92 95

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.
FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.
PATNA. THIRUVANANTHAPURAM.